



# CIREX Si Bouchepor W1

## Sealer

SHAKE THOROUGHLY BEFORE USE

### Description

**CIREX Si Bouchepor W1** is a water based sealer formulated for composite and metallic mould. It does not contain any solvent, which improves the environment of operators

### Advantages

**Cirex W1** reduces the fine porosities of the mould

It is used before the application of the release agent in order to increase its efficiency and provide an excellent base coat

Its solvent free composition allows an application without risk on PU primer or/and lacquer

### Application

1. Mould surface must be thoroughly cleaned with cleaner CIREX WATERNET, the CIREX Si 19 or any other efficient release agent cleaner
2. Apply with a cotton cloth or by spray 1- 2 coats of Cirex Si W1. Wait roughly 15 minutes between coats. After few minutes buff it in order to take off the surplus, spread the sealer properly hence a nice shine
3. Allow to cure for thirty minutes before applying the mould release agent.

### Spray Gun Application

Better to use a spray gun with touch-type nozzle from 0,8 to 1,8.

The pressure will be 0,6 to 1 bar maximum, according to the surface to be treated.

Average consumption: 8-12 ml / layer / m<sup>2</sup>

*This type of application also requires a light buffing of each layer*

### Packaging

1 liter / 0.84 kg	5 liters / 4.2 kg
-------------------	-------------------

### Storage

24 months in its original closed container

Keep away from frost and cold temperatures

Close back tightly after each use

### Note

After delivery, the use and storage of our products are no longer under our control, and we cannot longer accept any responsibility in regards to the products in any ways

Product technical information and data is based on the best information available and does not constitute or imply a warranty or patent infringement of any kind. The user is responsible for testing product suitability prior to use in production.